

SF

Part No. 213901, 213904, 213928 and 213934

DATASHEET

Pre-assembled induction loops

Induction loops to be used with induction loop detectors ProLoop

Technical data

Loop circumference	
- SF6/10	6 m
- SF8/10	8 m
- SF10/10	10 m
- SF12/15	12 m
Connection wire	
- SF6/10	10 m
- SF8/10	10 m
- SF10/10	10 m
- SF12/15	15 m
Cable diameter of the loop	
- SF6/10	5.4 mm
- SF8/10	5.4 mm
- SF10/10	5.4 mm
- SF12/15	4.9 mm
Cable diameter of the connection wire	
	6.1 mm
Loop cable	
- SF6/10	5 x 0.34 mm ²
- SF8/10	4 x 0.34 mm ²
- SF10/10	4 x 0.34 mm ²
- SF12/15	3 x 0.34 mm ²
Connection wire	
	2 x 0.75 mm ² , twisted, shielded
Loop inductance	
	80 – 300 µH
Material	
	PVC
Colour	
	grey



Ordering information

Article No.	
- SF6/10	213928
- SF8/10	213934
- SF10/10	213901
- SF12/15	213904
Loop resistance	
	< 8 Ω incl. loop lead-in
Compliance	
	RoHS directive 2011/65/EU

Ambient conditions

Operating temperature	-20°C to +70°C
Storage temperature	-40°C to +70°C
Rel. air humidity	< 95%, non-condensing

Box contents

Pre-assembled induction loop

Subject to change without notice

00007124A 27/19