

Part number

# MLP 10 LS220



Surface mounting housing, IL-BRID series,  
with 1 lever, M20 x 2 cable entry, size  
"57.27", with metal cover

| Product description                    |                             | Material properties          |                                                                  |
|----------------------------------------|-----------------------------|------------------------------|------------------------------------------------------------------|
| Product type                           | Surface mounting housing    | Other materials              | Lever: Polyamide (PA) and Stainless steel core<br>Gasket: Rubber |
| Series                                 | IL-BRID                     | Colour                       | RAL 7040 grey                                                    |
| Closing type                           | With 1 lever                | RoHs conformity              | Compliant                                                        |
| Size                                   | Size 57.27                  | China RoHs - EFUP            | E                                                                |
| Cable entry                            | With cable entry<br>M20 x 2 | REACH SVHC substances        | No                                                               |
| Specification                          | With metal cover            | Approvals / Standards        |                                                                  |
| Technical data                         |                             | Certifications               | DNV, BV                                                          |
| IP degree of protection                | IP65 / IP66 / IP69          | UL                           | ECBT2                                                            |
| Further technical details              |                             | cUL                          | ECBT8                                                            |
| Weight                                 | 257,50 g                    | General ordering information |                                                                  |
| Operating temperature range (min, max) | -40°C...+125°C              | EAN13 code                   | 8015747288613                                                    |
|                                        |                             | eCl@ss 8.1                   | 27440202                                                         |
|                                        |                             | ETIM 7.0                     | EC000437                                                         |
| Packaging Information                  |                             |                              |                                                                  |
| Packaging length                       | 300,00 mm                   | Packaging height             | 160,00 mm                                                        |
| Packaging width                        | 180,00 mm                   | Packaging weight             | 2,84 kg                                                          |
| Packaging volume                       | 8,64 dm³                    | Packaging description        | Carton box                                                       |
| Packaging quantity                     | 10 Pcs                      | Packaging EAN code           | 8015747108775                                                    |
| Sub-packaging weight                   | 1,42 kg                     | Sub-packaging description    | Plastic packaging                                                |
| Sub-packaging quantity                 | 5 Pcs                       | Sub-packaging EAN barcode    | 8015747108782                                                    |

Part number

# MLP 10 LS220



Catalogue drawings

