

Part number

MAPN 10.32



Surface mounting housing, LS-TYPE series, with 2 levers, M32 cable entry, size "57.27", high construction

Product description

Product type	Surface mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 57.27
Cable entry	With cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	380,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHS conformity	Compliant
China RoHS - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	CQC, DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163125
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Packaging length	475,00 mm
Packaging height	200,00 mm
Packaging width	150,00 mm
Packaging weight	5,10 kg
Packaging volume	14,25 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747249164
Sub-packaging weight	2,55 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187657

Part number

MAPN 10.32



Catalogue drawings



CH..N - MA, MF..N enclosures size "57.27" LS-TYPE version

inserts:	page	housings with double lever	hoods with 4 pegs
CDD 42 poles + Ⓛ 61 *			
CQE 18 poles + Ⓛ 81 *			
CSH 10 poles + Ⓛ 89 *			
CCE 10 poles + Ⓛ 90 *			
CNE, CSE, JONE, JCSE 10 poles + Ⓛ 97 and 107 *			
CSS 10 poles + Ⓛ 119 *			
CTE, CTSE **) 10 poles + Ⓛ 127 *			
CMSE 3+2 (aux) poles + Ⓛ 135			
CMCE 3+2 (aux) poles + Ⓛ 134 *			
CX 8/24 poles + Ⓛ 151 *			
MIXO 3 modules 160x195 *			

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 10	M	MFON 10.32	M
surface mounting housing, high construction, with 2 levers	MAPN 10.32	32	MHON 10.25	25
with pegs, side entry			MFON 10.32	32
with pegs, side entry, high construction			MHVN 10.25	25
with pegs, top entry			MFVN 10.32	32
with pegs, top entry, high construction				

**) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions in mm

CHIN 10	MAPN 10.32	MFON 10.32	MHON 10.25	MHVN 10.25	MFVN 10.32

dimensions shown are not binding and may be changed without notice

Notes

Dimensions shown in mm are not binding and may be changed without notice.